

**DANNEMANN
SIEMSEN
BIGLER &
IPANEMA MOREIRA**

10/557538

IAP20 Rec'd PCT/PTO 21 NOV 2005

Code: 311878001

World Intellectual Property Organization
(WIPO)
34, Chemin des Colombettes
CH-1211 Geneva 20
Suíça

PROPRIEDADE INDUSTRIAL

Eduardo Dannemann (1919 - 1959)
Catharina Bigler (1947 - 1981)
Carl Buschmann (1900 - 1941)
Luiz de Ipanema Moreira (1927 - 1990)

Conselheiros

Gert Egon Dannemann
M. Pestana da Silva Netto
Samir Said Matheus
Tannay de Farias

Rio de Janeiro

Peter Dirk Siemsen
David Merrylees
Gisela Fischer
José Antonio B. L. Faria Correa
Luiz Henrique O. do Amaral
Maria Thereza M. Wolff

Raul Hey

Carlos Cezar Cordeiro Pires
Ivan Bacellar Ahert
Maria Carmen de Souza Brito
Peter Eduardo Siemsen
Elisabeth Siemsen do Amaral
Ana Lúcia de Sousa Borda
Carla Tiedemann C. Barreto
Atílio José Ventura Gorini
A. Weber N. Milagre
José Eduardo Campos Vieira
Jorge Knauss de Mendonça
Semir da Silva Fonseca
Alvaro Loureiro Oliveira

Rafaela Borges Walter Carneiro
Roger Charles Taylor Troth
Joaquim Eugenio Goutart
José Henrique Vasi Werner
Marcos Velasco Figueiredo
Rodrigo Borges Carneiro
Mauro Ivan C. R. dos Santos
Maria Edina de O. C. Portinari

Renata Hohl

Manuela Romana Gomes Carneiro
Márcia de Oliveira Anechinno
André Luiz Souza Alvarez
Eduardo da Gama Camara Junior
Sydineia de Souza Trindade
Sandra Leis

Roberto da Silveira Torres Junior
Jussara Tolentino N. Trindade
Tânia Lúcia B. Engelke
Roberta X. da S. Calazans
Rodrigo Rocha de Souza
Filipe Fonteles Cabral
Rafael Dias de Lima
Flávia C. de C.M. Amaral
Cândida Ribeiro Caffé
Rita Capra Vieira
André Ferreira Oliveira
Sabrina Cassará

Mariana A. G. de Souza Starling
José Eduardo de V. Pieri
Markus Michael de M. Wolff
Maurício Teixeira Desiderio
Volkhard Hanewald
Bruno Lopes Hoffinger

Gustavo Heitor P. L. de Andrade
Amâncio Paulo Neto
Alexia Maria de Aragão da Costa
Rafael Alab de Araujo

Paulo Roberto Diamante

Consultores

Marco Antonio Gonçalves
José Marcelo de O. Fernandes
Marcella Souza G. B. Freire

São Paulo

Gustavo de Freitas Moraes
Henrique Steuer I. de Mello
Frank Fischer
Marina Inês Fuzila Karakanian

Luiz Gonzaga M. Lobato
Daniela Thompson S. Martinez
Sandra Brandão de Abreu
Cláudio França Loureiro
Franklin Batista Gomes
Ana Carolina Lee Barbosa
Luís Carlos S. Duarte
Bruno Falcone

Consultores

Gabriela S. Neves
Paula Santos e Silva
Ana Claudia Mamede Carneiro

Agente da Propriedade Industrial
Registro nº 192
Associado a A.B.A.P.I.

P005271-

Rio de Janeiro

RUA MARQUÊS DE OLINDA, 70 - 22251-040 RIO DE JANEIRO - RJ - BRASIL
C. POSTAL (P.O. BOX) 2142 - 20001-970 RIO DE JANEIRO - RJ - BRASIL
TEL.: (+55) 21 2553 1811
FAX: (+55) 21 2553 1812 & (+55) 21 2553 1813
mail@dannemann.com.br

São Paulo

AV. INDIANÓPOLIS, 739 - 04063-000 SÃO PAULO - SP - BRASIL
C. POSTAL (P.O. BOX) 57065 - 04093-970 SÃO PAULO - SP - BRASIL
TEL.: (+55) 11 5575 2024
FAX: (+55) 11 5549 2300
spmail@dannemann.com.br

<http://www.dannemann.com.br>

cooling compressors.

Brief Description of the Invention

The objectives of the present invention are achieved by means of a sensor assembly, to measure the movements of a fluid pump, the fluid pump being actuated by an electric motor and the electric motor being connectable to a feed voltage, the sensor comprising an accelerometer that is electrically associated to a bias circuit, the accelerometer configuring first and second acceleration transducers, and comprising a feed terminal and a signal terminal, the feed terminal being electrically connectable to the motor feed voltage, and the signal terminal being electrically connectable to an external measuring circuit.

The objectives are also achieved by means of a fluid pump comprising a cylinder, a piston, a housing comprising a fluid-tight terminal hermetically enclosing the cylinder and the piston, thus forming a hermetic assembly, the piston being actuated by an electric motor, the electric motor being linked to an electric voltage by means of a pair of voltage terminals associated to the hermetic terminal, the fluid pump comprising a sensor assembly associated to the cylinder, the sensor assembly comprising a feed terminal and a signal terminal, the feed terminal being connectable to one of the voltage terminals and the signal terminal being electrically connectable to an external measuring circuit, the sensor assembly comprising a bias circuit associated to the accelerometer, the bias circuit being mounted in an internal portion of the housing.

The objectives of the present invention are further achieved by means of a cooler having a sensor assembly that measures movements of the fluid pump, the fluid pump being actuated by an electric motor and the electric motor being connectable to a feed voltage, the sensor assembly comprising an accelerometer and wherein the accelerometer is electrically associated to a bias circuit, wherein the latter comprises a feed terminal and a signal terminal, the feed terminal being electrically connectable to the feed voltage of the motor, and the signal terminal being electrically connectable to the external measuring circuit.

Brief Description of the Drawings

The present invention will now be described in greater detail with

connected to the measuring circuit (55).

7. A sensor assembly according to claim 6, characterized in that the bias circuit (51) comprises a transistor (51a) operatively associated to the signal terminal (33) and to the feed terminal (34).

5 8. A sensor assembly according to claim 7, characterized in that the external measuring circuit (55) comprises a microprocessor (52), the microprocessor (52) measuring the signal of the sensor assembly (1) by means of the signal terminal (33).

9. A fluid pump (10) comprising:

10 - a cylinder (58),
 - a piston (57), and
 - a housing (50) comprising a hermetic terminal (60) and hermetically enclosing the cylinder (58) and the piston (57), forming a hermetic assembly (100),

15 the piston (57) being driven by an electric motor (30), the electric motor (30) being connected to an electric voltage (V) by means of a pair of voltage terminals (61, 62) associated to the hermetic terminal (60),

20 the fluid pump (10) being characterized by comprising a sensor assembly (1) associated to the cylinder (58), the sensor assembly (1) comprising a feed terminal (34) and a signal terminal (33), the feed terminal (34) being connected to one of the voltage terminals (61, 62) and the signal terminal (33) being electrically connectable to an external measuring circuit (55),

25 the sensor assembly (1) comprising a bias circuit (51) associated to the accelerometer (2), the bias circuit (51) being mounted in an internal portion (50') of the housing (50).

10. A fluid pump according to claim 9, characterized in that the sensor assembly (1) comprises an accelerometer (2) associated to a support means (3), the support means (3) being fixed to the hermetic assembly (100).

30 11. A fluid pump according to claim 10, characterized in that the sensor assembly (1) comprises a base portion (3a), the base portion (3a) being fixedly associable to the hermetic assembly (100).

12. A fluid pump according to claim 11, characterized in that the sensor assembly (1) comprises a weight (2a), connected to a first insulating element (20') and to a second insulating element (20''), first and second acceleration transducers (4a, 4b), a feed terminal (34) and a signal terminal (33) projecting from the first and second acceleration transducers (4a, 4b).

13. A fluid pump according to claim 12, characterized in that the first insulating element (20') is positioned on the surface (3a) of the support of the sensor assembly (1).

14. A fluid pump according to claim 13, characterized in that the first and second acceleration transducers (4a, 4b), the second insulating element (20'') and the weight (2a) are positioned overlapping the first insulating element (20').

15. A fluid pump according to claim 14, characterized in that the bias circuit (51) comprises a transistor (51a) operatively associated to the signal terminal (33) and to the feed terminal (34).

16. A fluid pump according to claim 15, characterized in that the external measuring circuit (55) comprises a microprocessor (52), the microprocessor (52) measuring the signal of the sensor assembly (1) by means of the signal terminal (33).

17. A fluid pump according to claim 16, characterized in that the housing (50) comprises a hermetic terminal (60) for passage of the feed terminal (34) and signal terminal (33).

18. A cooler characterized by comprising a sensor assembly (1), as defined in claims 1 to 9.